



- ▶ No pressure loss
- ▶ High Accuracy
- ▶ Wide Turndown Ratio
- ▶ Robust Design
- ▶ High Response Time and Repeatability

▶ General Information

DOMA series compact induction flow meter is designed for exact measurement of various fluids during the batching process, namely their lower amounts with a very high accuracy and repeatability of 0.1%. Possible applications are such as filling bottles, cups and pots with dairy products or with other products intended for sale.

The meter is delivered without a display with 12 to 24V DC power supply. Furthermore, it is equipped with an input signal for synchronization of the measuring cycle with the start of batch but it can also serve as a control signal for starting the batch from the parent system. The pulse output can indicate the total flow or it can be used to control valve. The operation of LED serves for clear evaluation of the meter's readout.



▶ Technical Features

Measuring Range	0,3...10 m/sec
Supply Voltage	12...24VDC
Output	Pulse 1,6 KHz
Tmax	100°C
Pmax	40 bar
Flow Accuracy	±0,5% of Reading
Protection	IP67

▶ Ordering

DOMA		Description
Transmitter		Blind Transmitter, no display
Line Size	006	DN6
	010	DN10
	015	DN15
	020	DN20
	025	DN25
	032	DN32
	040	DN40
	050	DN50
Connection	W	Wafer
	T	Threaded
	C	Clamp Connection

