



- %2,5 accuracy of F.S.
- Compact Desing
- Easy to Read
- All Stainless Steel Wetted Parts

➤ Description

FIKD Series Target Flow meters are fit for the measurement of liquid in pipes. The advantage is it can be installed from any direction, neglecting the influence of liquid. FIKD Series Target Flow meters can display current flow rate of volume and total as optionally.

➤ Technical Specifications

Turndown Ratio	15-100%
Min. Flow Rate	1.5-10m ³ /h
Max. Flow Rate	185-1300 m ³ /h
Output (optional)	Limit switch or 4-20mA
Accuracy	±%2.5 F.S.
Max Pressure	DN50-DN80: PN40 DN100-DN200: PN16 DN250-DN400: PN10
Medium Temperature	-40°C to 120°C
Operating Temperature	-25°C to 65°C
Humidity	≤85%
Protection Class	IP65
Storage Temperature	-20°C to 80°C
LCD display	Optional rate and total





- %2,5 accuracy of F.S.
- Compact Desing
- Easy to Read
- All Stainless Steel Wetted Parts

➤ Description

FIKD Series Target Flow meters are fit for the measurement of liquid in pipes. The advantage is it can be installed from any direction, neglecting the influence of liquid. FIKD Series Target Flow meters can display current flow rate of volume and total as optionally.

➤ Technical Specifications

Turndown Ratio	15-100%
Min. Flow Rate	1.5-10m ³ /h
Max. Flow Rate	185-1300 m ³ /h
Output (optional)	Limit switch or 4-20mA
Accuracy	±%2.5 F.S.
Max Pressure	DN50-DN80: PN40 DN100-DN200: PN16 DN250-DN400: PN10
Medium Temperature	-40°C to 120°C
Operating Temperature	-25°C to 65°C
Humidity	≤85%
Protection Class	IP65
Storage Temperature	-20°C to 80°C
LCD display	Optional rate and total

